

Air-termination rods

FL 88 Air-termination mast, freestanding



Characteristics
Set including connection clamp and accessories kit. Dimensioned according to SIA 261 for wind load up to 1.1kN/m2 (150km/h)
Icon D mm = utility space

Article-Nr.	E-Number									
272.863.002	156 953 210	AI	3000	10 - 30	25	2	6	720		1
272.863.004	156 953 220	AI	3500	10 - 30	35	3	6	720		1
272.863.006	156 953 230	AI	4000	10 - 30	45	3	6	720		1
272.863.008	156 953 240	AI	4500	10 - 30	60	4	6	720		1
272.863.010	156 953 250	AI	5000	10 - 30	80	6	6	720		1

Technical Specifications: **Air-termination mast, freestanding FL 88**

	272.863.002	272.863.004	272.863.006	272.863.008
Material	Al			
Height H	3000 mm	3500 mm	4000 mm	4500 mm
External diameter	10 - 30 mm			
Socket weight	25 kg	35 kg	45 kg	60 kg
Number of Cantilever	6			
Number of Sockets	2	3		4
Surface protection	unbehandelt			
High-voltage-proof insulated model	No			
Connection	Round conductor			
Model	Interception rod with tripod			
Diameter D	720 mm			
Commercial specification				
Customs number	85389000			
country of origin	CE			

	272.863.010
Material	Al
Height H	5000 mm
External diameter	10 - 30 mm
Socket weight	80 kg
Number of Cantilever	6
Number of Sockets	6
Surface protection	unbehandelt
High-voltage-proof insulated model	No
Connection	Round conductor
Model	Interception rod with tripod
Diameter D	720 mm
Commercial specification	
Customs number	85389000
country of origin	CE

