

Deep earthing components

■ LR 3 Cable



**Characteristics**  
Special copper stranded conductor, single wire Ø 3mm

| Article-Nr. | E-Number    |  |  |  |  |  |  |  |  |  |
|-------------|-------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--|--|--|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 265.052.000 | 156 990 630 | ok                                                                                | Cu                                                                                | 50                                                                                | 9.5                                                                               |  |  |  | 14.7                                                                                | 6                                                                                   |



Technical Specifications: **Cable LR 3**

|                                  |                    |
|----------------------------------|--------------------|
| Article No.                      | 265.052.000        |
| Suitable for use in soil         | ok                 |
| Material                         | Cu                 |
| Nominal cross section conductor  | 50 mm <sup>2</sup> |
| Number of strands                | 7                  |
| Application lightning protection |                    |
| External diameter                | 9.5 mm             |
| Diameter fibres                  | 3 mm               |
| Surface protection               | unbehandelt        |
| Material coating                 | None               |
| Cross section                    | 50 mm <sup>2</sup> |
| Commercial specification         |                    |
| Customs number                   | 74130000           |
| country of origin                | CE                 |
| Logistic specification           |                    |
| VPE Weight                       | 6.24 kg            |

