

Conductor connections and junctions

■ AV 25 Connecting lug



**Legend**  
a) for isolated fall protection, side length to middle hole 70mm

| Article-Nr. | E-Number    |  |  |  |  |  |  |  |  |
|-------------|-------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 270.055.002 | 156 801 300 | H                                                                                 | InoxA2                                                                            | M8x30                                                                             | 6 - 10                                                                            | 16.5                                                                              | 90                                                                                  |                                                                                     | 25                                                                                  |

Technical Specifications: **Connecting lug AV 25**

|                                   |               |
|-----------------------------------|---------------|
| Article No.                       | 270.055.002   |
| Approved class H / N (EN 62561-1) | H             |
| Material                          | InoxA2        |
| Wire diameter                     | 6 - 10 mm     |
| Eyelet diameter                   | 16.5 mm       |
| Screw                             | M8x30         |
| Deflection (angle)                | 90 °          |
| Type of connector                 | Access-clip   |
| Type of fastening screws          | Hexagon screw |
| Surface protection                | unbehandelt   |
| required torque                   | 12 N·m        |
| Commercial specification          |               |
| Customs number                    | 85389000      |
| country of origin                 | CH            |
| Logistic specification            |               |
| VPE Weight                        | 2.98 kg       |

