

Conductor connections and junctions

■ AV 24 Connector for profile rails



**Characteristics**  
With hammer head screws for profile rails.

| Article-Nr. | E-Number    |  |  |  |  |  |  |  |  |
|-------------|-------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 260.062.053 | 156 831 480 | H                                                                                 | InoxA2                                                                            | M8x40                                                                             | 10 - 12                                                                           | 95                                                                                | 20                                                                                  | 35                                                                                  | 50                                                                                  |

Technical Specifications: **Connector for profile rails AV 24**

|                                   |                                     |
|-----------------------------------|-------------------------------------|
| Article No.                       | 260.062.053                         |
| Approved class H / N (EN 62561-1) | H                                   |
| Material                          | InoxA2                              |
| Screw                             | M8x40                               |
| Wire diameter                     | 10 - 12 mm                          |
| Nominal cross section conductor   | 95 mm²                              |
| Type of connector                 | Connection clamp                    |
| Type of fastening screws          | Hexagon screw                       |
| Suitable for connection           | Round conductor Rd 10-12 / Rd 10-12 |
| Surface protection                | unbehandelt                         |
| Length a                          | 20 mm                               |
| Width b                           | 35 mm                               |
| required torque                   | 12 N·m                              |
| Commercial specification          |                                     |
| Customs number                    | 85389000                            |
| country of origin                 | CH                                  |
| Logistic specification            |                                     |
| VPE Weight                        | 8.5 kg                              |

