

Conductor connections and junctions

■ AV 26 Contact clip



Characteristics
With connection terminal for longitudinal and transversal wiring.
Not to be used in the ground.

Article-Nr.	E-Number									
280.105.001	156 831 000	H	InoxA2	6 - 10	20 - 40					10
280.105.002	156 831 050	H	InoxA2	6 - 10	20 - 80					10
280.105.003	156 831 080	H	InoxA2	6 - 10	20 - 120					10
280.105.004	156 831 090	H	InoxA2	6 - 10	20 - 180					10
280.105.005	156 832 370	H	InoxA2	6 - 10	20 - 250					10

Technical Specifications: **Contact clip AV 26**

	280.105.001	280.105.002	280.105.003	280.105.004
Approved class H / N (EN 62561-1)	H			
Material	InoxA2			
Wire diameter	6 - 10 mm			
External diameter	20 - 40 mm	20 - 80 mm	20 - 120 mm	20 - 180 mm
Cross section of the connecting conductors	25 - 50 mm²			
Clamping/chucking range	20 - 40 mm	20 - 80 mm	20 - 120 mm	20 - 180 mm
Number of conductors	1			
Surface protection	unbehandelt			
required torque	15 N·m			
Commercial specification				
Customs number	85389000			
country of origin	CH	CE		
Logistic specification				
VPE Weight	1.515 kg	1.604 kg	1.61 kg	1.74 kg

	280.105.005
Approved class H / N (EN 62561-1)	H
Material	InoxA2
Wire diameter	6 - 10 mm
External diameter	20 - 250 mm
Cross section of the connecting conductors	25 - 50 mm²
Clamping/chucking range	20 - 250 mm
Number of conductors	1
Surface protection	unbehandelt
required torque	15 N·m
Commercial specification	
Customs number	85389000
country of origin	CE
Logistic specification	
VPE Weight	1.95 kg

