

Anchorage points

EAP Quattro Single anchorage point



**Characteristics**  
Curved single anchorage point Quadro made of Inox A2 for a rotatable screw connection on thread M16  
incl. connection for the H-tested integration in lightning protection

| Article-Nr. | E-Number |  |  |  |  |  |  |  |  |  |
|-------------|----------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--|--|--|-------------------------------------------------------------------------------------|
| 310.000.007 |          | H                                                                                 | InoxA2                                                                            | 60                                                                                | 135                                                                               | 4                                                                                 |  |  |  | 10                                                                                  |

| Accessories                                                                                              |             |                                                                                   |                                                                                   |                                                                                   |                                                                                   |  |  |  |  |                                                                                     |
|----------------------------------------------------------------------------------------------------------|-------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--|--|--|--|-------------------------------------------------------------------------------------|
|  Connection cable FL 16 |             |                                                                                   |                                                                                   |                                                                                   |                                                                                   |  |  |  |  |                                                                                     |
| Article-Nr.                                                                                              | E-Number    |  |  |  |  |  |  |  |  |  |
| 280.103.011                                                                                              | 280.103.011 | H                                                                                 | CuvSn                                                                             | 16                                                                                | 800                                                                               |  |  |  |  | 10                                                                                  |
| 280.103.012                                                                                              | 156 940 390 | H                                                                                 | CuvSn                                                                             | 16                                                                                | 1200                                                                              |  |  |  |  | 10                                                                                  |

Technical Specifications: **Single anchorage point EAP Quattro**

|                                   |             |
|-----------------------------------|-------------|
|                                   | 310.000.007 |
| Approved class H / N (EN 62561-1) | H           |
| Material                          | InoxA2      |
| Height H                          | 60 mm       |
| External diameter                 | 135 mm      |
| Number of person                  | 4           |
| Commercial specification          |             |
| Customs number                    | 73089000    |
| country of origin                 | CH          |
| Logistic specification            |             |
| VPE Weight                        | 4.31 kg     |

